

# Package: packageDiff (via r-universe)

September 13, 2024

**Title** Compare R Package Differences

**Version** 0.2

**Date** 2020-04-06

**Description** It provides utility functions for investigating changes within R packages. The pkgInfo() function extracts package information such as exported and non-exported functions as well as their arguments. The pkgDiff() function compares this information for two versions of a package and creates a diff file viewable in a browser.

**Imports** diffr, htmlwidgets

**License** GPL (>= 2)

**Depends** R (>= 2.10)

**URL** <https://github.com/couthcommander/packageDiff>

**Encoding** UTF-8

**RoxygenNote** 6.1.1

**Repository** <https://couthcommander.r-universe.dev>

**RemoteUrl** <https://github.com/couthcommander/packagediff>

**RemoteRef** HEAD

**RemoteSha** b9b7f9a42830c677f0f56dde3a9c2bb82a2fe9f8

## Contents

packageDiff-package	2
pkgDiff	3
pkgInfo	4
print.pkgInfo	5
unzipPackage	6

## Index

7

---

**packageDiff-package      *Package Diff***

---

**Description**

It provides utility functions for investigating changes within R packages. The `pkgInfo` function extracts package information such as exported and non-exported functions as well as their arguments. The `pkgDiff` function compares this information for two versions of a package and creates a diff file viewable in a browser.

**Details**

This package is experimental. Please submit bugs to <https://github.com/couthcommander/packageDiff>.

**Author(s)**

Cole Beck <cole.beck@vumc.org>

Maintainer: Cole Beck <cole.beck@vumc.org>

**See Also**

Useful links:

- <https://github.com/couthcommander/packageDiff>

**Examples**

```
tar1 <- system.file("examples", "yaml_2.1.18.tar.gz", package = "packageDiff")
tar2 <- system.file("examples", "yaml_2.1.19.tar.gz", package = "packageDiff")
a <- pkgInfo(tar1)
b <- pkgInfo(tar2)
pkgDiff(a, b)

a <- pkgInfo('https://cran.r-project.org/src/contrib/Archive/yaml/yaml_2.1.18.tar.gz')
b <- pkgInfo('https://cran.r-project.org/src/contrib/Archive/yaml/yaml_2.1.19.tar.gz')
pkgDiff(a, b)
```

---

**pkgDiff***Package Diff*

---

**Description**

This function compares version changes within packages.

**Usage**

```
pkgDiff(a, b, doc = TRUE, src = TRUE, vignettes = TRUE,  
       tests = TRUE, demo = TRUE, width = 80)
```

**Arguments**

a	First package, a ‘pkgInfo’ object.
b	Second package, a ‘pkgInfo’ object.
doc	Include documentation in diff output.
src	Include src files in diff output
vignettes	Include vignette files in diff output
tests	Include test files in diff output
demo	Include demo files in diff output
width	Output width.

**Details**

Generate diffs between package information.

**Value**

‘diffr’ object is open in browser

**Examples**

```
tar1 <- system.file("examples", "yaml_2.1.18.tar.gz", package = "packageDiff")  
tar2 <- system.file("examples", "yaml_2.1.19.tar.gz", package = "packageDiff")  
a <- pkgInfo(tar1)  
b <- pkgInfo(tar2)  
pkgDiff(a, b)
```

---

**pkgInfo**                   *Extract Package Information*

---

**Description**

This function extracts information from an R package.

**Usage**

```
pkgInfo(pkg, leaveRemains = FALSE)
```

**Arguments**

<code>pkg</code>	The compressed (tar.gz) build file of an R package.
<code>leaveRemains</code>	Keep decompressed package in temp directory.

**Details**

Generate package information from its build file.

**Value**

<code>Package</code>	Package name
<code>Version</code>	Version number
<code>Imports</code>	Imported packages
<code>Suggests</code>	Suggested packages
<code>ImportedFunctions</code>	Functions imported from other packages
<code>ExportedFunctions</code>	Functions exported from package
<code>AllFunctions</code>	All defined functions
<code>FormalArgs</code>	Function arguments
<code>Data</code>	Dimension information on data sets
<code>documentation</code>	Full package documentation
<code>source</code>	Files in src directory
<code>vignettes</code>	Files in vignettes directory
<code>tests</code>	Files in tests directory
<code>demo</code>	Files in demo directory

## Examples

```
tarfile <- system.file("examples", "acepack_1.3-3.3.tar.gz", package = "packageDiff")
info <- pkgInfo(tarfile)

url <- 'https://cran.r-project.org/src/contrib/Archive/acepack/acepack_1.3-3.3.tar.gz'
info <- pkgInfo(url)
```

---

print.pkgInfo      *Print Package Information*

---

## Description

Print method for ‘packageInfo’ class.

## Usage

```
## S3 method for class 'pkgInfo'
print(x, doc = FALSE, src = FALSE,
      vignettes = FALSE, tests = FALSE, demo = FALSE, ...)
```

## Arguments

x	A packageInfo object.
doc	Include documentation in output.
src	Include src files in output.
vignettes	Include vignette files in output.
tests	Include test files in output.
demo	Include demo files in output.
...	Additional parameters, unused at this time.

## Details

Print its argument and return it invisibly.

## Examples

```
tarfile <- system.file("examples", "acepack_1.3-3.3.tar.gz", package = "packageDiff")
pkgInfo(tarfile)

url <- 'https://cran.r-project.org/src/contrib/Archive/acepack/acepack_1.3-3.3.tar.gz'
info <- pkgInfo(url)
print(info)
```

---

**unzipPackage**

*Extract R Package*

---

## Description

Untar an R package into a temp directory.

## Usage

```
unzipPackage(x)
```

## Arguments

x	The compressed (tar.gz) build file of an R package, either local or URL.
---	--

## Value

List of files extracted.

## Examples

```
tarfile <- system.file("examples", "acepack_1.3-3.3.tar.gz", package = "packageDiff")
info <- unzipPackage(tarfile)
```

# Index

packageDiff (packageDiff-package), 2

packageDiff-package, 2

pkgDiff, 3

pkgInfo, 4

print.pkgInfo, 5

unzipPackage, 6